



209 SERIES

Shallow Economy Wraparound



A shallow economy designed wraparound luminaire now available including T8 LED bypass lamps. Flexible design allows for 2 lamp or 4 lamp versions in 2 foot or 4 foot lengths. Using T8 LED Lamps, provides for low initial fixture cost, maintenance free operation and delivers excellent brightness. The QUIK LED/X1LED wraparound 9 inch fixture is extremely energy efficient and does not require a ballast or driver. Since this wraparound does not use a ballast or driver the only component that will ever need changing is the LED T8 Lamp. The lamps are warranteed for five years. This fixture has the flexibility to change: wattage, lumens and color temperature by simply changing the lamps without needing an electrician.

LAMP

2 or 4 lamp positions

CONSTRUCTION

Completely die formed from heavy gauge cold rolled steel. Design embossed ends are locked and secures to the housing. Wireway cover snaps on or off without tools

MOUNTING

Suitable for individual or continuous run installations. May be surface or pendant mounted.

DIFFUSERS

A crystal clear diffuser extruded from 100% virgin acrylic that will maintain its color under normal conditions, indefinitel . Linear prisms on the interior side walls direct the light ceilingwards, which can then refract back down, The bottom is composed of an evenly spaced pattern of conical prisms yielding low brightness, glarefree diffused light. Diffuser is lift and shift for ease of relamping and cleaning and is capable of hanging down from either side of the housing.

SIZE W x L x H in inches

2 Lamp - 9.375W x 48L x 3.1Dp (4ft.)

X1 LED / QUIK LED

The most economical, practical and user friendly series of LED fixtures offering energy savings, quality of light, and long life. With no ballast to manage, X1LED/Quik LED creates a new fixture with hassle-free maintenance. X1 LED fixtures are UL Listed with the latest LED T8 Bypass lamps. Replace Flourescent Lamps and remove the Ballast and enjoy over 40% energy savings and reduced operating costs! This system offers the maximum flexibility fand as T8 LED Lamp Technology continues to improve • imply change the lamp to achieve additional energy savings A lamp has lamp to achieve additional energy savings A mperature Simple, Easy & Long Lasting!

Lamp Specifcations:

Our T8 LED lamps are available in 2 or 4 ft sizes in different wattage, lumens and color temperature options. Savegreen Lighting is a premier supplier of LED T8 lamps and makes a variety of Bypass T8 lamps to meet the needs of your special application. Options include more energy efficient 1 , 15W and 17W lamps with Premium 10 Year warranty as well as high output options up to 3500 lumens. Double ended LED T8 lamps are also available. See lamp options and specs at www.savegreenlighting.com.

Optional Dimming Options:

The 4 FT lamps are available with two dimming options; Specially designed dimming lamps require an external driver that runs 1 or 2 lamps. So more than 2 lamps require multiple external drivers or Consult for Bypass Type B lamps that can be dimmed without any external driver and dim with standard 2 wire dimming. See dimming options and specs at www. saylite.com.

Emergency Options:

The standard X1 LED Lamps require an inverter or an All-inone emergency kit that includes LED array, battery and driver. Dimmable T8 LED with external driver works with standard LED EM. For a 5 watt inverter that is similar to adding a 500 Lumen emergency in a conventional fluorescent fixture, ad "INV5W" to the end of the item number. This will allow 5 watts of one lamp to work in emergency mode. Or add "EMKT12" to the end of the item number to get a 12W stand alone emergency kit in the fixture that comes with a driver, battery and small LED array that works in Emergency mode. Ask your sales representative for additional information on Eergency Options.



I SG Inside

LITE Technology 2055 Luna Rd. Suite 142 Carrollton, TX 75006

Phone: 972-247-3171 ext 2056

www.litetechnology.com email: info@litetechnology.com

Catalog Number:

Notes:





Ordering Options

(Fixtures below include LED T8 Lamp LT8ABP48L18W2250LXXK. For Other Lamp Options See below and Replace LNXXX with short code below. Specifiy without Lamps by removing LNXXX

ITEM NO.	DESCRIPTION	
209A232AX1LN18W40	9" x 48" 4500 Lumen 2 Light Wraparound w/2x18W LED T8 4000K Lamps Included	

Change 40 to 35 or 50 for different Kelvin. Change Lamp attage to 13W on 2FT or 15W on 4FT

For 5W Emergency, Add INV5 at the End of Item Number for KTEMRGLED5500AC. For fixtures wired for double ended lamps, change X1 to X2 and see the Savegreen Lamps below for the proper Double Ended Lamp. For fixtures without lamps included, remove the "LNXXX" at the end of the item number and have X1 or X2 for Single or Double Ended wiring.

LN18W40 - Lamp Specification

50,000 Hour Life with 5 Year Warranty

Beam Angle 140 Degree

Aluminum Base and Aluminum Housing with Glass Cover

Operating Temperature: - 20C to 50C Color Temperature: 3500K, 4000K, 5000K

G13 Pins (Same as Fluorescent Linear T8 Bipin)

AC100 - 277V without Ballast

Single Ended or Double Ended Power (If not specified use X1 Single Ended Power

Savegreen T8 or T5 LED Lamp Options

To include one of these lamps in fixture, remove "LNXXX" and add Savegreen Inside code belo. (See www.savegreenlighting.com for specification sheets or more information on these lamp options.

VERSION	SAVEGREEN INSIDE	SAVEGREEN ITEM NO.
Popular	SGB15W35	LT8BG48L15W1740LXXK
Standard	SGS29W35	LT8BGC24L9W1050LXXK
Standard	SGS312W35	LT8BGC36L12W1200LXXK
Standard	SGS15W35	LT8BGC48L15W1740LXXK
Premium	SGP12W35	L10T8BGC48L12W1750LXXK
Premium	SGP15W35	L10T8BGC48L15W2000LXXK
Premium	SGP18W35	L10T8BGC48L18W2500LXXK
High Output	SGH26W40	LT8BGC48L26W3500LXXK
Double Ended	SGD18W35	LT8BDGC48L18W2100LXXK
Т5НО	SGT525W40*	LT5BG46L25W3300LXXK
Magic	SGM18W35K	LT8ABP48L18W2250LXXK
Magic	SGM18W35K	LT8ABP48L15W1875LXXK
Magic	SGM215W35K	LT8ABP24L15W1875LXXK

Change 35 to 40 or 50 for different Kelvin. *For T5, CCT 40K and 50K available.

I SG

Catalog Number:
Notes:

LITE Technology

2055 Luna Rd. Suite 142 Carrollton, TX 75006

Phone: 972-247-3171 ext 2056

www.litetechnology.com email: info@litetechnology.com

Special __

Consult Lite for Options