

Series HSL CIT QUIK LED

Weatherproof Enclosure

X1 / EI = >76

Harsh Environment Enclosures



The Simple LED Solution

All the Benefits of LED with Ease, Practicality and Flexibility

FEATURES & SPECIFICATIONS

The HSL CITCL offers more versatility than other weatherproof enclosures. Poured in place gasket and cam latches seal the enclosures. The Mounting System can provide dramatic savings on the installation labor. Designed around T8 LED tubes, this fixture offers long term energy savings. Very tough diffusers resist breakage. The QUIK LED/ X1LED harsh environment enclosure fixtures utilize efficient LED T8 lamps that provide high lumen output with efficient energy savings. Since they don't require any ballast or driver the only component that will ever need changing is the LED T8 lamp. QUIK LED creates a new fixture with hassle-free maintenance, and as technologies improve simply changing the lamp offers a new look or more energy savings. The lamps are covered by a five year warranty. This system is economical, practical and user friendly.

LAMP

2, 3 or 4 lamp positions

MATERIALS & FEATURES

One piece compression molded polyester fiberglass housing with polycarbonate latches. Seamless continuously bonded poured-in-place polyurethane gasketing. Fixture component tray attaches fixture body with pinch-release clips. 1/2" conduit entry hole in each end of housing with weathertight plug.

- Stainless steel latch with "keeper" (optional)
- Latches can be tamper proof with #6 screw
- UL certified for wet locations

MOUNTING

Durable stainless steel mounting hardware. No holes ever have to be drilled through the housing for installation. Installation time is dramatically reduced. Optional stainless steel bail for chain hung installations.

DIFFUSER

Component tray provides high reflectance. 100% Impact modified UV stabilized acrylic linear ribbed lens with smooth exterior face for easy cleaning.

SIZE W x L x H in inches

7.30W X 48L X 4.12H

Lamp Specifications:

SAVEGREEN LIGHTING

Our T8 LED lamps are available in 2 or 4 ft sizes and in different wattages, lumens and color temperature options. Savegreen Lighting is a premier supplier of LED T8 lamps. We also offer some T8 LED Tubes with extended warranties. Check the website for all lamp options or consult your LITE sales specialist.

Savegreen T8 LED Lamp Information Below:

Lamps are DLC Listed
Lamps have a standard 5 year warranty
Warranty provided by: LITE Technology (a fleco co)

Optional Dimming: V@Á ÁVÁÁ] • ÁÁÁ
áááá | Á ááá { á * Á] á] • Á] ^ ááá Á
á ^ á } ^ ááá { á * Á] • Á ^ ááá Á
^ áá } ááá ^ ááá } • Á Á Á] • Á [ááá
• [^ Á] ^ ááá ááá } • Á Á Á á áá } Á Á
áá { [áá Á Á] • Á Á

FOR DIMMABLE VERSION:

Change X1 to JLDLV and LN18W to LN18D



Series HSL CITCL QUIK LED

X1 / EI \neq >76

Weatherproof Enclosure

Ordering Options

Fixtures below include LED T8 Lamp LT8ABP48L18W2100LXXK. For Other Lamp Options See below and Replace LNXXX with short code below. Specify without Lamps by removing LNXXX

ITEM NO.	DESCRIPTION
HSLCITCL232X1LN18W40	4ft. Enclosure w/Clear Lens 4200 Lumen 2x18W LED T8 4000K Lamps Included
HSLCITCL332X1LN18W40	4ft. Enclosure w/Clear Lens 63000 Lumen 3x18W LED T8 4000K Lamps Included
HSLCITLB2328X1LN18W4	8ft. Enclosure w/Linear Ribbed Lens 8400 Lumen 4x18W LED T8 4000K Lamps Included

HSLCITCL Series is available in both: 4' and 8' in a 1 Lamp Linear Profile. Change 232 or 2328 to 132 or 1328 for the 1 LAMP LINEAR Profile Option.

Change 40 to 35 or 50 for different Kelvin. Change Lamp Wattage to 15 W on 4ft. Consult for different lens options, sensors and lengths.

For 5W Inverter Emergency, Add INV5 at the End of Item Number. Or, Add KT-EMRG-12-1200-K1 for EM Kit.. For other options consult LITE sales. For fixtures wired for double ended lamps, change X1 to X2 and see the Savegreen Lamps below for the proper Double Ended Lamp. For fixtures without lamps included, remove the "LNXXX" at the end of the part number and have X1 or X2 for Single or Double Ended wiring.

FOR DIMMABLE VERSION: Change X1 to JLDMMV and LN18W to LN18D Example: RDI332JLDMMVLN18D35K

LN18W40 - Lamp Specification
50,000 Hour Life with 5 Year Warranty
Beam Angle 140 Degree
Aluminum Base and Aluminum Housing with Glass Cover
Operating Temperature: - 20C to 50C
Color Temperature: 3500K, 4000K, 5000K
G13 Pins (Same as Fluorescent Linear T8 Bipin)
AC100 – 277V without Ballast
Single Ended or Double Ended Power (If not specified use X1 Single Ended Power)

Savegreen T8 or T5 LED Lamp Options

To include one of these lamps in fixture, remove "LNXXX" and add Savegreen Inside code below.
(See www.savegreenlighting.com for specification sheets or more information on these lamp options.)

VERSION	SAVEGREEN INSIDE	SAVEGREEN ITEM NO.
Popular	SGB15W35	LT8BG48L15W1740LXXK
Standard	SGS29W35	LT8BGC24L9W1050LXXK
Standard	SGS312W35	LT8BGC36L12W1200LXXK
Standard	SGS15W35	LT8BGC48L15W1740LXXK
Premium	SGP12W35	L10T8BGC48L12W1750LXXK
Premium	SGP15W35	L10T8BGC48L15W2000LXXK
Premium	SGP18W35	L10T8BGC48L18W2500LXXK
High Output	SGH26W40	LT8BGC48L26W3500LXXK
Double Ended	SGD18W35	LT8BDGC48L18W2100LXXK
T5HO	SGT525W40*	LT5BG46L25W3300LXXK
Magic	SGM18W35K	LT8ABP48L18W2250LXXK
Magic	SGM18W35K	LT8ABP48L15W1875LXXK
Magic	SGM215W35K	LT8ABP24L15W1875LXXK

Change 35 to 40 or 50 for different Kelvin.
*For T5, CCT 40K and 50K available.



Consult Factory for Dimmable Lamp Options. Dimmable lamps that operate on Drivers carry a 5 year Warranty.

Special
WARRANTY

Consult Lite for Options

