

CATALOG#:
PROJECT:
TYPE:

# Series HSL CV300

# LED LARGE CANOPY

The HSL CV300 Series Large Canopy luminaire is available for surface. This fixture was created with an optical distribution designed specifically to replace HID lighting systems up to 175w MH or HPS. Typical lighting applications include retail centers, industrial parks, schools and universities, public transit and airports, office buildings and medical facilities. Mounting heights of 12 to 20 feet can be used based on light level and uniformity requirements.


#### Finish:

Textured Architectural Powdercoat Finish Over a Chromate Conversion Coating. Custom Colors Available Upon Request.

#### **Listing & Ratings:**

CSA: Listed for Wet Locations, ANSI/UL 1598, 8750. (Damp Locations When Used with VNQM.) IP65 Sealed LED Compartment.

#### **Order Information Example:** HSL CV300 HSL CV300 1X45 Model **Optics** Wattage CCT Color Driver Lens **Options** HSLCV300 F=Type V 1X45=45w U=120-277V 4K=4000K S=Standard Clear Z=Bronze Consult Factory LED Large Canopy H=347-480V 5K=5000K Polycarbonate Prismatic Lens C=Custom W=White (Consult Factory) for pricing and lead



LITE Technology

2055 Luna Rd. Suite 142 Carrollton, TX 75006

Phone: 972-247-3171 ext 2056

www.litetechnology.com email: info@litetechnology.com



# **FEATURES & BENEFITS**

# Housing:

Die Cast Aluminum Housing, ½" Coin Plugs with O-rings for Conduit & Photocell on Two Sides & Back, Nickel-Plated Stainless Steel Hardware.

#### Lens:

Standard Clear Polycarbonate Prismatic

## Mounting Options:

Mount Directly Over a 4" Recessed Outlet Box, or Use ½" Surface Conduit or Quick-Mount Bracket.

### Controls:

Fixtures Ordered with Factory-Installed Photocell or Motion Sensor Controls are Internally Wired for Switching.Consult Factory for your desired options. Fixtures are NOT Designed for Use with Line Voltage Dimmers.



# **Warranty:**

5-Year Warranty for -40°C to +40°C Environment.

