



Series HSL DC

Medium and Large Outdoor Wall Packs

FEATURES & SPECIFICATIONS

INTENDED USE

The DC Series is an Indoor/Outdoor Bronze Wall Pack that is offered in multiple sizes and wattages. Used to replace 100W MH and 400W MH, the DC Series boasts a Lumen output of 4900-16400 with efficacy up to 115 Lumens per Watt. Our optional Photocell and Motion Sensor supports the Emergency Battery, ensuring illumination whenever you need it. This fixture is ideal for building entryways and walkways, security, pathway, and perimeter applications. UL/cUL wet location and DLC qualified.

OPTIONS AND ACCESSORIES

This luminaire has options that include a PIR Sensor, Emergency Battery, and Photocell. Contact factory for more details and customization.



MATERIALS & FEATURES

- •Sealed, die-cast housing
- Polycarbonate optical lens with UV stabilizers
 - Operating Temperature is -40°C to 40°C (-40°C to 104°F)
- •120-277V, 0-10 Dimmable
 - •Optional Photocell and/or Motion Sensor
- •Optional 90-Minute, 8W 900L Emergency


MOUNTING


Our DC is designed for surface or J-Box mounting applications.


Ordering Example: HSL DC200E-90W11200L-MV-50K

SERIES		WATTAGE AND LUMEN PACKAGE		DRIVER		KELVIN TEMPERATURE		OPTIONS	
DC150SR	Medium LED Wall Pack	45W4900L	45 Watts, 4900 Delivered Lumens	MV	Multi-Volt 120-277V	40K	4000K		Occupancy Sensor* Photocell
		45W4950L	45 Watts, 4950 Delivered Lumens	MV	Multi-Volt 120-277V	50K	5000K	EM	Emergency
		70W7900L	70 Watts, 7900 Delivered Lumens	MV	Multi-Volt 120-277V	50K	5000K		
DC200E	Large LED Wall Pack	90W11200L	90 Watts, 11200 Delivered Lumens	MV	Multi-Volt 120-277V	50K	5000K		*Only Available with DC150SR*
		135W16400L	135 Watts, 16400 Delivered Lumens	MV	Multi-Volt 120-277V	50K	5000K		


Medium Size (45W/70W)










Large Size (90W/135W)







Weight



LITE Technology

Phone: 972-247-3171 ext 2056

www.litetechnology.com email: info@litetechnology.com