

HSL - EWP Series

LED ENGINEERED WRAPAROUND WITH SOLID ENDS

FEATURES & SPECIFICATIONS

INTENDED USE Heavy duty construction ideal for individual or continuous runs with solid ends. Engineered wraparound high efficiency luminaire available in either four or eight foot lengths. Low initial cost, maintenance free, this series also delivers excellent brightness control.

SIZE W x L x H in inches (mm)

9.56"W x 48"L x 3.19"Dp (4ft.)

9.56"W x 96"L x 3.19"Dp (8ft.)

CONSTRUCTION


Completely die formed from heavy gauge cold rolled steel. Design embossed ends are locked and secures to the housing. Wireway cover snaps on or off without tools.

MOUNTING

Suitable for individual or continuous run installations. May be surface or pendant mounted.

Typical Options and Accessories

EM - Emergency battery backup, WP - whips.



DIFFUSERS

A crystal clear diffuser extruded from 100% virgin acrylic that will maintain its color under normal conditions, indefinitely. Linear prisms on the interior side walls direct the light ceilingwards, which can then refract back down. The bottom is composed of an evenly spaced pattern of conical prisms yielding low brightness, glarefree diffused light. Diffuser is lift and shift for ease of relamping and cleaning and is capable of hanging down from either side of the housing.

ORDERING INFORMATION

Example: EWPLR48LS32W3450LDMV40K

STANDARD

HSL EWP		LR		L48		S34W3450L		DMV		40K	
Series		LR		Size		Wattage and Lumen		Driver		Kelvin Temperature	
HSLEWP		LR		48L 48"		S32W3450L 32 System Watts, 3450 Delivered Lumens		DMV 0-10V Dimming		30K 3000K	
						S48W4800L 48 System Watts, 4800 Delivered Lumens				35K 3500K	
						H72W7000L 72 System Watts, 7000 Delivered Lumens				40K 4000K	
										50K 5000K	
		LR									
		Linear Ribbed Lens									
				96L 96"		S48W4800L 48 System Watts, 4800 Delivered Lumens					
						S65W7000L 65 System Watts, 7000 Delivered Lumens					
						S97W9600L 97 System Watts, 9600 Delivered Lumens					

Plug in system Options

Part Number	Descriptions
PI1	3 Wires Harness, Including White, Black and Green
PI2	4 Wires Harness, Including White, Black, Green and Blue for Emergency Battery Backup
PI3D	5 Wires Harness, Including White, Black, Green, Violet and Gray

*** Consult Factory for more options**

LITE TECHNOLOGY
2055 Luna Rd. Suite 142 Carrollton, TX 75006
Phone: 972-247-3171 ext 2056 www.litetechnology.com
email: Info@litetechnology.com

Catalog Number:

Notes: