

Series HSL FHB & FHBFR

Haybay Baffle or Lens Fixture

HSL FHB Series

Highbay Baffle or Lens



FEATURES & SPECIFICATIONS

INTENDED USE

The FHB & FHBFR Series is offered with a baffle or with a lens (in door frame). The baffles cut glare and provide a sleek appearance. The Lens option offers even light distribution from a very efficient fixture body. This fixture dresses up any space and is great for: Retail, Office, or even Industrial applications. Premium full specular white reflectors are standard for high efficiency lighting; other reflectors may be specified for wider distributions. Mounting options include direct surface, chain, or pendant wire, but is not suitable for stem mount.

Mounting

Surface mount or chain hung. See end of chapter T02Strip for accessory mount kits.

SIZE W x L x H in inches (mm)

4ft. - 11.25W x 48L x 4.25H

8ft. - 11.25W x 96L x 4.25H

DIMENSIONS

All dimensions are inches. Specifications subject to change without notice

MATERIALS & FEATURES

Housing is die-formed and embossed code 22 gauge steel. Finish is high reflectance baked white enamel. Wiring knockouts are provided on back and end of housing. Baffle is hinged and latched, and may be hinged from either side. Premium full specular enhanced white reflectors are available.

ORDERING INFORMATION

STANDARD 4'

Example: HSL FHBL48LS57W6400LW30DMV40K

HSL FHB	L	48L	S57W6400L	W30	DMV	40K
Series		Size	Wattage and Lumen	Driver	Color Temperature	
HSL FHB Wide Body Strip		48L 48"	S32W4050L 32 System Watts, 4050 Delivered Lumens S48W5650L 48 System Watts, 5650 Delivered Lumens S57W6400L 57 System Watts, 6400 Delivered Lumens	DMV 0-10V MV Multi - Volt 120V-277V	30K 3000K 35K 3500K 40K 4000K 50K 5000K	
Baffle or Lens				Reflector		Options
L Baffle included FR Lens Included X No Baffle				W30 White Steel Reflector		CS 5-15P 120V 8ft. Cord & Plug CS12 L7-15P 277V 8ft. Cord & Plug CS08 8ft. Cord, No Plug WP 6 ft. 3 wire, Whip WP10 6 ft. 4 wire, Whip

Series HSL FHB & FHBFR

Linear Highbay with Baffle or Lens

HIGH OUTPUT 4'

Example: HSL FHBL48LH72W8200LW30DMV40K

HSL FHB	L	48L	H72W8200L	W30	DMV	40K	
Series HSL FHB Wide Body Strip	Baffle or Lens L Baffle included FR Lens Included X No Baffle	Size 48L 48"	Wattage and Lumen H72W8200L 72 System Watts, 8200 Delivered Lumens	Reflector W30 White Steel Reflector	Driver DMV 0-10V MV Multi - Volt 120V-277V	Color Temperature 30K 3000K 35K 3500K 40K 4000K 50K 5000K	Options CS 5-15P 120V 8ft. Cord & Plug CS12 L7-15P 277V 8ft. Cord & Plug CS08 8ft. Cord, No Plug WP 6 ft. 3 wire, Whip WP10 6 ft. 4 wire, Whip

ORDERING INFORMATION

STANDARD 8'

Example: HSL FHBL96LS97W11300LW30DMV40K

HSL FHB	L	96L	S97W11300L	W30	DMV	40K	
Series HSL FHB Wide Body Strip	Baffle or Lens L Baffle included FR Lens Included X No Baffle	Size 96L 96"	Wattage and Lumen S97W11300L 97 System Watts, 11300 Delivered Lumens S114W12800L 114 System Watts, 12800 Delivered Lumens	Reflector W30 White Steel Reflector	Driver DMV 0-10V MV Multi - Volt 120V-277V	Color Temperature 30K 3000K 35K 3500K 40K 4000K 50K 5000K	Options CS 5-15P 120V 8ft. Cord & Plug CS12 L7-15P 277V 8ft. Cord & Plug CS08 8ft. Cord, No Plug WP 6 ft. 3 wire, Whip WP10 6 ft. 4 wire, Whip

HIGH OUTPUT 8'

Example: HSL FHBL48LH144W16450LW30DMV40K

HSL FHB	L	96L	H144W16450L	W30	DMV	40K	
Series HSL FHB Wide Body Strip	Baffle or Lens L Baffle included FR Lens Included X No Baffle	Size 96L 96"	Wattage and Lumen H144W16450L 144 System Watts, 16450 Delivered Lumens	Reflector W30 White Steel Reflector	Driver DMV 0-10V MV Multi - Volt 120V-277V	Color Temperature 30K 3000K 35K 3500K 40K 4000K 50K 5000K	Options CS 5-15P 120V 8ft. Cord & Plug CS12 L7-15P 277V 8ft. Cord & Plug CS08 8ft. Cord, No Plug WP 6 ft. 3 wire, Whip WP10 6 ft. 4 wire, Whip