

Series HSL FSF LED Strip with Lens

Economical & Flexible LED Strip with Lens: 2' 4' & 8'

FEATURES & SPECIFICATIONS

Great Performance Strip Fixture - now available with Lens. This LED offering is perfect for so many applications. Designed

economically yet with balance and sleek aesthetics. This fixture is perfect for: Retail, Industrial, Back House applications as well as the perfect solution for mezzanine low ceiling installations where a wide distribution light pattern is needed. 5 year factory warranty.

MOUNTING

Surface mount, chain hung, double stem.

TYPICAL OPTIONS AND ACCESSORIES Whips,

wireguards, Emergency battery backup (IOTA ILB-CP10HE), or contact factory for more details.

LED Medium Body Strip with Lens



SIZE*

W x L x H in inches

2ft: 4.25W x 24.00L x 3.25H 4ft: 4.25W x 48.00L x 3.25H 8ft: 4.25W x 96.00L x 3.25H

* All dimensions are inches. Specifications subject to change without notice

ORDERING INFORMATION

2 ft - STANDARD

Example: HSL FSFFR24LZ33W3300LDMV40K

HSL FSF		FR	24	I L	Z33V	V3300L	DMV		40)K	
Series		Lens	Lei	ngth	Wattage	and Lumen	Drive	er]	Kelvin	Temp	Options
FSF	FR	Frosted Lens	24L	24"	J14W1400L	14 System Watts, 1400 Delivered Lumens	0-10V Dim	5	30K 35K	3000K 3500K	WP 6 ft. 3 wire 18 gauge whip WP10 6 ft. 4 wire 18 gauge whip
Med Body Strip SMFSF					J18W1800L	18 System Watts, 1800 Delivered Lumens			40K 50K	4000K 5000K	EM10HE 10w Emerg battery backup
Med Body Strip w/ Microware Sensor					Z28W2800L	28 System Watts, 2800 Delivered Lumens				2	MDT4 Occupancy Sensor
Wilcioware Sensor					Z33W3300L	33 System Watts,					

LITE Technology

2055 Luna Rd. Suite 142 Carrollton, TX 75006

Phone: 972-247-3171 ext 2056

www.litetechnology.com email: info@litetechnology.com





Series HSL FSF Strip

LED Strip with Lens: 2' 4' & 8'

HSL FSF Series

LED Medium Body Strip with Lens

ORDERING INFORMATION

Example: HSL FSFFR48LJ31W3100LDMV40K

4 ft - STANDARD

HSL FSF	FR	48L	J31	W3100L		DMV	40	K
Series	Lens	Length	Wattag	e and Lumen		Driver	Kelvin Te	mperature
FSF	FR Frosted Lens	48 L 48"	J28W2800L	28 System Watts, 2800 Delivered Lumens	DMV	0-10V Dimming	30K 35K	3000K 3500K
Medium Body Strip SMFSF			J31W3100L	31 System Watts, 3100 Delivered Lumens			40K 50K	4000K 5000K
Medium Body Strip with			Z48W4800L	48 System Watts, 4800 Delivered Lumens			2011	Options
Microware Sensor			Z57W5700L	57 System Watts, 5700 Delivered Lumens			WP	6 ft. 3 wire 18 gauge wh
			Z61W6100L	61 System Watts, 6100 Delivered Lumens				6 ft. 4 wire 18 gauge wh
							EM10	10w Emergency battery backup
							EM12	12w Emergency battery backup
							MDT4	Occupancy Sensor

8 ft - STANDARD

Example: HSL FSFFR96LJ48W4800LDMV40K

H <u>SL FSF</u>	FR	96L	J48W	'4800L		DMV	40	<u>K</u>
Series	Lens	Length	Wattage a	and Lumen		Driver	Kelvin Tei	nperature
FSF	FR Frosted Lens	96L 96"	J48W4800L	48 System Watts, 4800 Delivered Lumens	DMV	0-10V Dimming	30K 35K	3000K 3500K
Medium Body Strip SMFSF			J57W5700L	57 System Watts, 5700 Delivered Lumens			40K 50K	4000K 5000K
Medium Body Strip with			J61W6100L	61 System Watts, 6100 Delivered Lumens				Options
Microware Sensor			Z97W9700L	97 System Watts, 9700 Delivered Lumens			WP	6 ft. 3 wire 18 gauge v
			Z114W11400L	114 System Watts, 11400 Delivered Lumens			WP10	6 ft. 4 wire 18 gauge v
							EM10	10w Emergency battery backup
							EM12	12w Emergency battery backup
							MDT4	Occupancy Sensor



2055 Luna Rd. Suite 142 Carrollton, TX 75006

Phone: 972-247-3171 ext 2056

www.litetechnology.com email: info@litetechnology.com

