

HSL LTX SERIES

1 Light LED DECO Strip



X1LED LED DECO strip is the ideal light for many residential applications like kitchens and utility rooms and many other commercial applications. The X1LED LED DECO strip utilizes efficient LED T8 lamps that provide high lumen output with efficient energy savings. Consult factory for optional reflectors and tandem configurations. Since they don't require any ballast or driver the only component that will ever need changing is the LED T8 lamp. The lamps are warranted for five years.

LAMP

1 lamp position

CONSTRUCTION

- Housing is die-formed and embossed code 22 gauge cold roll steel
- Finish is high reflectance baked white enamel
- Fixture wraps around cleanly hide sockets
- Functional end caps protect sockets from impact and are removable to access wire way
- Easy mounting through provided holes in housing
- Included 5 foot suspension hardware kit

MOUNTING

Pendant mount

SIZE W x L x H in inches

4' - 1.75" x 48.45" x 2.375"

QUIK LED

The most economical, practical and user friendly series of LED fixtures with the energy savings, quality of light, long life and hassle-free maintenance. QUIK LED fixtures are UL Listed with the latest LED T8 Bypass lamps. Fixtures provide over 44% energy savings over comparable fluorescent fixtures utilizing less expensive fixtures than the fluorescent version (no ballast required) and have flexibility to change wattage and color temperature any time. Fixture performance will evolve over time with the evolution of the T8 LED lamp technology. Concerned about maintenance with an LED array and driver fixture, QUIK LED solves that by utilizing a self contained LED lamp that fits into fixture just like a fluorescent lamp.

Lamp Specifications:

Our T8 LED lamps are available in 4 ft sizes in different wattage, lumens and color temperature options. Savegreen Lighting is a premier supplier of LED T8 lamps and makes a variety of Bypass T8 lamps to meet the needs of your special application. Options include more energy efficient 12W, 15W and 17W lamps with Premium 10 Year warranty as well as high output options up to 3500 lumens. Double ended LED T8 lamps are also available.

Optional Dimming Options:

The 4 FT lamps are available with two dimming options; Specially designed dimming lamps require an external driver that runs 1 or 2 lamps. So more than 2 lamps require multiple external drivers or Consult for Bypass Type B lamps that can be dimmed without any external driver and dim with standard 2 wire dimming.

Emergency Options:

The standard QUIK LED Lamps require an inverter or an All-in-one emergency kit that includes LED array, battery and driver. Dimmable T8 LED with external driver works with standard LED EM. For a 5 watt inverter that is similar to adding a 500 Lumen emergency in a conventional fluorescent fixture, add "INV5W" to the end of the item number. This will allow 5 watts of one lamp to work in emergency mode. Or add "EMKT12" to the end of the item number to get a 12W stand alone emergency kit in the fixture that comes with a driver, battery and small LED array that works in Emergency mode.



Catalog Number:
Notes:

Ordering Options

(Fixtures below include LED T8 Lamp LT8ABP48L18W2250LXXK. For Other Lamp Options See below and Replace LNXXX with short code below. Specify without Lamps by removing LNXXX)



Chrome Finish



White Finish

ITEM NO.	DESCRIPTION
HSLLTx132x1CHLN18W40K	48" Linear Pendant 2100 Lumens 1x18W LED T8 Chrome
HSLLTx132x1WHLN18W40K	48" Linear Pendant 2100 Lumens 1x18W LED T8 White

Change 40 to 35 or 50 for different Kelvin. Change Lamp Wattage to 13W on 2FT or 15W on 4FT

For 5W Emergency, Add INV5 at the End of Item Number for KTEMrgLED5500AC.
 For fixtures wired for double ended lamps, change QUIK to X2 and see the Savegreen Lamps below for the proper Double Ended Lamp. For fixtures without lamps included, remove the "LNXXX" at the end of the item number and have QUIK or X2 for Single or Double Ended wiring.

LN18W40 - Lamp Specification
 50,000 Hour Life with 5 Year Warranty
 Beam Angle 140 Degree
 Aluminum Base and Aluminum Housing with Glass Cover
 Operating Temperature: - 20C to 50C
 Color Temperature: 3500K, 4000K, 5000K
 G13 Pins (Same as Fluorescent Linear T8 Bipin)
 AC100 – 277V without Ballast
 Single Ended or Double Ended Power (If not specified use QUIK Single Ended Power)

Savegreen T8 or T5 LED Lamp Options

To include one of these lamps in fixture, remove "LNXXX" and add Savegreen Inside code below.
 (See www.savegreenlighting.com for specification sheets or more information on these lamp options.)

VERSION	SAVEGREEN INSIDE	SAVEGREEN ITEM NO.
Popular	SGB15W35	LT8BG48L15W1740LXXK
Standard	SGS29W35	LT8BGC24L9W1050LXXK
Standard	SGS312W35	LT8BGC36L12W1200LXXK
Standard	SGS15W35	LT8BGC48L15W1740LXXK
Premium	SGP12W35	L10T8BGC48L12W1750LXXK
Premium	SGP15W35	L10T8BGC48L15W2000LXXK
Premium	SGP18W35	L10T8BGC48L18W2500LXXK
High Output	SGH26W40	LT8BGC48L26W3500LXXK
Double Ended	SGD18W35	LT8BDGC48L18W2100LXXK
T5HO	SGT525W40*	LT5BG46L25W3300LXXK
Magic	SGM18W35K	LT8ABP48L18W2250LXXK
Magic	SGM18W35K	LT8ABP48L15W1875LXXK
Magic	SGM215W35K	LT8ABP24L15W1875LXXK

**10-YEAR
WARRANTY**

Change 35 to 40 or 50 for different Kelvin.
 *For T5, CCT 40K and 50K available.



Catalog Number:
Notes: