

## SERIES HSL LVS

### Louvered 8" Decorative Linear



A direct/indirect lighting fixture that makes a bold statement, complementing design elements such as stone, metal, brick and glass. Industrial look provides a modern aesthetic. Available with slots in reflector for indirect light or solid reflector. Available standard in galvanized steel finish or powder coated black. Mounts with cable kit. Louver is matte silver anodized parabolic. The QUIK LED LVS series utilize efficient LED T8 lamps that provide high lumen output with efficient energy savings. Since they don't require any ballast or driver the only component that will ever need changing is the LED T8 lamp. The lamps are warranted for five years. Unlike LVS series that utilize LED arrays and drivers these fixtures have the flexibility to change wattage, lumens, and color temperature simply by changing the lamps without the need to call a licensed electrician.

#### LAMP

2 lamp positions, Available in T8

#### HOUSING

Die-formed cold rolled steel body with heavy duty construction. Mates with Parabolic louver.

#### LOUVER

Matte silver anodized, parabolic. with optional slots on the side of louver. End cap complete the finished louvered look.

#### MOUNTING

Fixtures can be surface mounted to the ceiling or pendant hung by stem or cable. Welded heavy gauge steel flanges can be ordered to accept 3/8" threaded stems. Alignment brackets are available for continuous row mounting.

#### SIZE W x L x H in inches (mm)

8"W x 49"L x 6.5H

#### QUIK LED

The most economical, practical and user friendly series of LED fixtures with the energy savings, quality of light, long life and hassle-free maintenance. QUIK LED fixtures are UL Listed with the latest LED T8 Bypass lamps. Fixtures provide over 44% energy savings over comparable fluorescent fixtures utilizing less expensive fixtures than the fluorescent version (no ballast required) and have flexibility to change wattage and color temperature any time. Fixture performance will evolve over time with the evolution of the T8 LED lamp technology. Concerned about maintenance with an LED array and driver fixture, QUIK LED solves that by utilizing a self contained LED lamp that fits into fixture just like a fluorescent lamp.

#### Lamp Specifications:

Our T8 LED lamps are available in 2 or 4 ft sizes in different wattage, lumens and color temperature options. See lamp options and specs. 50,000 Hour Life with 5 Year Warranty

Beam Angle 140 Degree

Aluminum Base and Aluminum Housing with Glass Cover Operating Temperature: - 20C to 50C

Color Temperature: 3500K, 4000K, 5000K

G13 Pins (Same as Fluorescent Linear T8 Bipin)

AC100 – 277V without Ballast

Single Ended or Double Ended Power (If not specified use QUIK Single Ended Power)

#### Optional Dimming Options:

The 4 FT lamps are available with a dimming option. Specially designed dimming lamps require an external driver that runs 1 or 2 lamps. So more than 2 lamps require multiple external drivers.

#### Emergency Options:

The standard QUIK LED Lamps require an inverter or an All-in-one emergency kit that includes LED array, battery and driver. Dimmable T8 LED with external driver works with standard LED EM it.

#### Ordering Options

(Fixtures below include LED T8 Lamp LT8ABP48L18W2250LXXK. For Other Lamp Options See below and Replace LNXXX with short code below. Specify without Lamps by removing LNXXX)

ITEM NO.	DESCRIPTION
LVS232X1WHLN18W40-HC301WH	48" LVS WHITE 4200 Lumen 2x18W LED T8 4000K Lamps included w/5 ft cable kit
LVS2328X1WHLN18W40-HC401WH	96" LVS WHITE 8400 Lumen 4x18W LED T8 4000K Lamps included w/5 ft cable kit

Change 40 to 35 or 50 for different Kelvin. Change Lamp Wattage to 13W on 2FT or 15W on 4FT  
Change WH TO BK (Black), IR (Iron), SL (Silver) or BR (Bronze)



For 5W Emergency, Add INV5 at the End of Item Number for KTEMRGLED5500AC. See other options at [www.saylite.com](http://www.saylite.com)

For fixtures wired for double ended lamps, change X1 to X2 and see the Savegreen Lamps below for the proper Double Ended Lamp. For fixtures without lamps included, remove the "LNXXX" at the end of the item number and have X1 or X2 for Single or Double Ended wiring.

### LN18W40 - Lamp Specification

50,000 Hour Life with 5 Year Warranty  
 Beam Angle 140 Degree  
 Aluminum Base and Aluminum Housing with Glass Cover  
 Operating Temperature: - 20C to 50C  
 Color Temperature: 3500K, 4000K, 5000K  
 G13 Pins (Same as Fluorescent Linear T8 Bipin)  
 AC100 – 277V without Ballast  
 Single Ended or Double Ended Power (If not specified use X1 Single Ended Power)

## Savegreen T8 or T5 LED Lamp Options

To include one of these lamps in fixture, remove "LNXXX" and add Savegreen Inside code below.

(See [www.savegreenlighting.com](http://www.savegreenlighting.com) for specification sheets or more information on these lamp options.)

VERSION	SAVEGREEN INSIDE	SAVEGREEN ITEM NO.
Popular	SGB15W35	LT8BG48L15W1740LXXK
Standard	SGS29W35	LT8BGC24L9W1050LXXK
Standard	SGS312W35	LT8BGC36L12W1200LXXK
Standard	SGS15W35	LT8BGC48L15W1740LXXK
Premium	SGP12W35	L10T8BGC48L12W1750LXXK
Premium	SGP15W35	L10T8BGC48L15W2000LXXK
Premium	SGP18W35	L10T8BGC48L18W2500LXXK
High Output	SGH26W40	LT8BGC48L26W3500LXXK
Double Ended	SGD18W35	LT8BDGC48L18W2100LXXK
T5HO	SGT525W40*	LT5BG46L25W3300LXXK
Magic	SGM18W35K	LT8ABP48L18W2250LXXK
Magic	SGM18W35K	LT8ABP48L15W1875LXXK
Magic	SGM215W35K	LT8ABP24L15W1875LXXK

10-YEAR  
**WARRANTY**

Change 35 to 40 or 50 for different Kelvin.  
 \*For T5, CCT 40K and 50K available.

