



HSL - S Series Narrow Body Strip

Narrow body one lamp strip for interior warehouse, retail, and utility areas requiring general illumination in a commercial quality narrow strip configuration. Economical two lamp versions also available.

Ordering Information

Example: HSL- S 125 X2 ZD(88141)

Series	Lamp Count	Lamp Type	Tandem Code [1]	Reflector	Ballast & Voltage [1]	Options
HSL S	1 17	24" T8		Blank No Reflector	S Residential 120V Ballast	WP 6ft. 3 wire, 18 gauge whip
Narrow Body Strip	1 25	6 36" T8	6' TandemStrip*	W30 White Steel reflector Standard mount	GMV Dimming Ballast for Phase or Two Wire Fluorescent Dimmers	WP10 6ft. 4 wire, 18 gauge whip
with or without reflectors	1 32	8 48" T8	8' TandemStrip*	W35 White Steel reflector Asymmetric	DMV Dimming ballast 0-10V	EM Emergency Ballast, 500 lumens
	1 59	96" F96T8 Slimline		M20 Mirrored reflector standard mount	X1 Wired for single ended LED T8 Lamps	EM14 Emergency Ballast, 1400 lumens
	1 14	22 in. T5 [4]	8' TandemStrip*	W10 White Aluminum reflector standard mount	X2 Wired for double ended LED T8 Lamps	D Ballast Disconnect
	1 21	34 in. T5[4]	8' TandemStrip*		Z GE Ballast	
	1 28	46 in. T5[4]			ZDMV LED Driver (# 88141)	
	1 24	22 in. T5HO [4]			ZDMV LED21T8/DR/D2L	
	1 39	34 in. T5HO [4]				
	1 54	46 in. T5HO [4]				
		LED Lamp options below: Must be paired with LED Driver				
	3	LED18T8/3/835 #82343				
	4	LED21T8/4/835 or 840	* (2 lamp positions total)			

Notes

- See end of T02Strip section for many additional lamps, ballasts, finishes and options
- Tandem doubles length and lamp count. Same lamps in cross section, additional lamps end to end
- Custom reflectors available to create any light distribution
- HiLume and LoLume ballasts available for T8 lamps only
- T5 & T5HO S body strips are full 24/36/48/96in. length. See KDS series for shorter strips.
- Review local codes and wiring limitations based on amperage capacity.

Wiring Harness Option - Continuous Run Application

Part #	Descriptions
P11	3 wire harness, including white, black and green
P12	3 wire harness, including white, black, green and blue for emergency battery backup
P13D	3 wire harness, including white, black, green, violet and gray

Add the accessories part number at the end to be factory installed

LAMP

- 1 lamp position

SIZE W X L X H in inches (mm)

- 2.80W x 1.60H
- Fixture length = lamp(s) length

MATERIALS & FEATURES

- Housing is die-formed and embossed code 22 gauge steel. Finish is high reflectance baked white enamel. Wiring knockouts are provided on back and end of housing. Ballast covers or reflectors attach without tools to simplify ballast access.
- Single unit length and tandem fixtures available in most lamp styles
- W3x, economical white steel reflectors, for abusive locations
- Two styles: symmetric and asymmetric End plate doubles as coupler for continuous row mounts
- M2, premium full specular (mirrored) reflectors, for maximum efficiency W1x. high reflectance white aluminum reflectors, combine economy and efficiency

ELECTRICAL

- Meets UL1598 for continuous row mounting and comes with provision for a coupling method. [6]

MOUNTING

- Surface mount, chain hung, double stem.

LISTING

- Fixture & Ballast: UL Listed Ballast: Thermally protected, class P, HPF, Non PCB unless otherwise specified

TYPICAL OPTIONS & ACCESSORIES

- Emergency ballasts, whips, fuses and wire guards.
- Contact factory for additional options.