

HSL SM302

Decorative Cut-Off Wall Pack

FEATURES & SPECIFICATIONS

- Heavy Duty Die Cast Aluminum Housing
- Tempered Glass Lens
- Die Cast Hinged Front & Rear Housings, Gasket Coin Plugs on Sides and Back
- Built-In Template for Mounting to Electrical Box
- Size: 18.0W x 7.35H x 9.0D
- Bronze Powder Coat Finish
- One Piece Anodized Aluminum Reflector
- Porcelain Socket & Bracket
- Meets Local "Dark Sky" Requirements
- Excellent for Use as an Uplight
- Lamps Included
- UL Listed (wet location)




ITEM NO.	DESCRIPTION
SM302L35W3456LMV50KBZ	18" x 7.25" x 9.0" / 35W, 2456L / 5000K / BRONZE
SM302LU5WD35WMV50KBZ	18" x 7.25" x 9.0" / UP, 5W, 480L / DOWN, 35W, 3456L / 5000K / BRONZE
SM302LU5WD70WMV50KBZ	18" x 7.25" x 9.0" / UP, 5W, 480L / DOWN, 70W, 6735L / 5000K / BRONZE

Item	Specification
Input Voltage	120-277V, 50/60Hz
LED CRI	75
Fixture CRI	73.5
LED Color Temperature	5000K
Fixture Color Temperature	5412
Fixture Lumens	2476 Lumen
Kit Lumens Outside Fixture	3501 Lumen
Lumen Maintenance	≥ 70% @ 5 years
Fixture Efficacy	56.20 Lumen/Watt
Zonal Lumen Requirement	0-90; 100% 80-90 <10%
Warranty	5 Years
LED Quantity (Brand:Cree)	32
LED TMP Temperature @25°C	74.5°C
Input Power	44W
Driver Efficiency	88%
Power Factor @277V	0.954
THD@277V	14.86%
Driver TMP temp @25° Ambient	55.6°C
Noise	<24dB
EMI	FCC part 15
Max Operating Temperature	45°C Ambient
Min Operating Temperature	-40°C
LED Lighting Assembly Dimen	11.375"H x 9.55"Wx6.758"D



**LED
Array**



LED FIXTURE INCLUDES:

- Two-Output Channel, Class 2 LED Driver, Model Number: AC-D18C350UVH
- Aluminum LED Driver Bracket
- 2 PCB LED Arrays with 32 Cree MX-3 LEDs



WARRANTY

Saylite warrants to the purchaser that this LED Fixture will be free from defects in material or workmanship for a period of 5 years from date of manufacture, when operated at a maximum ambient temperature of 110°F or 45°C, when properly installed and under normal conditions of use.