

## model WPL LED WALL PACK

### FEATURES & SPECIFICATIONS

- High Quality Die Cast Housing
- Chip and Fade resistant Bronze Powder-Coat Finish
- Sealed Borosilicate Glass Lens
- Highly Specular Forward Throw Reflector.
- Gasket Sealed Driver Enclosure
- 90 Degree Adjustability of Beam Angle with Full Cut Off Option
- High Power Citizen COB LED's
- Ultimate Versatility Allows Wall, Post or Bollard, and Horizontal Floodlight Installations.
- UL /cUL LISTED
- Photocell included



#### 90 Degree Beam Angle



- Size: 6.22W x 6.25H x 8.54D

#### Full Cut Off Beam Angle



- Size: 6.22W x 7.22H x 3.81D

EX: WPL6L14W1164LMV50KBZ

### ORDERING INFORMATION

Series	Wattage	@ a Yb	Driver	7c'cf'HYa dYfh fY	: ]b]g\
K D@ @	14W - 14 Wattage	1164L - 1164 Lumen	MV - 120-277V	50K - ) \$\$\$?	BZ - 6fcbnY'
K D@ @	&\$W - 20 Wattage	1848L - 1848 Lumen	MV - 120-277V	50K - ) \$\$\$?	BZ - 6fcbnY'
K D@ @	29W - 29 Wattage	2346L - 2346 Lumen	MV - 120-277V	50K - ) \$\$\$?	BZ - 6fcbnY'